

## NEW PETROL RANGE OF GENSETS FROM INDIA'S #1 GENSET BRAND

- Easy Key Start
- Stable Output with Silent Design
- Highest Rated Power Output
- Easy Maneuverability
- International Standard Output Plug
- Recoil Start as Standard Option
- Compliant to revised emission norms





KOEL Chhota Chilli Portable Petrol Gensets come from the house of Kirloskar, India's #1 Genset brand. Specialised in manufacturing of generators for more than seven decades, KOEL offers a wide range of

power solutions upto 5200 kVA. When it comes to Power, no one knows Gensets better than KOEL. This all new Petrol Genset is the latest addition to this illustrate portfolio.

Don't just limit your power backup to 4 lights & 4 fans. With the highest rated power in the segment, the choices of connecting several devices are more. User friendly KOEL Chhota Chilli Petrol Gensets with superior



durability & reliability ensures smooth and clean power to all connected devices.



Enjoy the benefits of mobility and portability. KOEL Chhota Chilli rolls on wheels and is equipped with a wide length handle. Now you carry power with you for a beach party or

a jungle camp. This feature is of great help for small establishments and mobile workshops too!

With the introduction of KOEL Petrol Gensets, the choice of power is now unlimited. From the lowest rating of 2.1 till 10 kVA, across the range of KCC products the choice of power



selection is now in your hands. Choose a genset from the widest range as per your ideal power needs.



KOEL Chhota Chilli Gensets reach you through a widest network of authorized dealers and are supported by over 5000 skilled service engineers spread across

India. Quality of service and response time is centrally monitored by KOEL. Dial the toll-free number and our authorized representative will be promptly available at your door step!

		PETROL G	IENSEI		
Product Name			KP2800	KP3300	KP5000
Genset Model			KCC-P-2.1 AS	KCC-P-3.0 AS	KCC-P-4.0 AS
Rated output at rated rpm		kW	2.1	3	4
Maximum Output		kVA	2.4	3.3	5
Rated Current		Α	8.34	13	17.4
Frequency		Hz	50	50	50
Voltage		V		Single Phase AVR Type	
Governing (As per ISO 8528 Part-V class)			G2	G2	G2
Sound Power Level LWA		dBA	≤ 86	≤ 86	≤ 86
Noise Level (1M) - for Reference		dBA	71	71	71
Fuel Consumption#	At 100 % Load	Ltrs/Hr	1.29	2.1	3.3
	At 75 % Load		1.09	1.7	2.6
	At 50 % Load		0.84	1.3	2.0
Fuel tank capacity		litres	6.5	12.5	12.5
Weight of genset with canopy (approx) ^	Dry	kg	110	129	145
Overall dimensions of genset	Length	mm	950	1045	1045
	Width	mm	510	550	550
	Height	mm	650	735	735
		ENGII	T .		
Engine Model			CCP196	CCP302	CCP389
Rated output (prime continuous rating		kW	2.9	4.2	5.6
as per ISO 3046)		HP	4.0	5.7	7.6
No. of cylinder		Nos	1 196	302	389
Cubic capacity  Rated Speed		cc RPM	3000	3000	3000
Bore & Stroke		KEW	68X54	80 X 60	88X64
Compression Ratio			8.3 (± 1):1	8.3 (± 1):1	8.3 (± 1):1
Cooling System			Air Cooled	Air Cooled	Air Cooled
Ignition System			TCI	TCI	TCI
Type			4 Stroke OHV		
Spark Plug			MICO Super MICO Super MICO Supe		MICO Super
Starting System			Electric/Recoil Start		•
Lub Oil change period#		hr	100	100	100
Lub Oil Sump Capacity		Lit	0.6	1.1	1.1
		ALTERN	ATOR		
Insulation Class			Class H	Class H	Class H
Alternator Efficiency ( 100 % )			74%	74%	74%
Max Voltage Dip at Full Load 0.8 pf Lag			<u>≤</u> 20 %	<u>≤</u> 20 %	<u>≤</u> 20 %
Max Time to build up rated voltage at Rated RPM			< 5 sec provided engine reach the rated speed		
		BATTE	RY		
Electrical Battery starting voltage			12	12	12
		FEATU	DEC		

## Typical appliance configuration



\* Applicable only for 3kW & 4kW. Condit

## Notes

- ^ Tolerances Apply
- # NTP

This Genset Model will be available in 4 Wheel configuration

Product improvement is a continuous process. Kindly contact KOEL for latest information

- Ahmedabad: 079 2692 9687/89 Bengaluru: 080 490 31130 Bhubaneshwar: 0674 258 8047 Chennai: 044 237 44624 Delhi: 011 2871 5826
- Guwahati: 0361 245 7616 Indore: 0731 3913100 Jaipur: 0141 2370007 Kochi: 0484 238 5757 Kolkata: 033 217 0858 Lucknow: 0522 274 1442
- Ludhiana: 0161 254 6668 / 69 Meerut: 0121 240 1199 Mumbai: 022 6151 1234 Patna: 0612 222 0412 Pune: 020 2581 0341
- Secunderabad: 040 275 34176 / 97

## KIRLOSKAR OIL ENGINES LIMITED

Laxmanrao Kirloskar Road, Khadki, Pune 411 003 INDIA.

www.koelgreen.com



koel.helpdesk@kirloskar.com